





PowerBully 12 RT Versatility in application. Sensitive for the environment.

The PowerBully 12 RT is the strong, robust, low ground pressure tracked carrier with high payload that embraces the challenge of unusual applications. Spacious cab, fuel efficient power train, rugged undercarriage and rubber track are complimented by quality workmanship with attention to detail and vehicle safety.

The low ground pressure functionality of the 12RT, in combination with versatility in application, make it the right choice. Wet soils, steep slopes, sidehills, sensitive subsoils, undeveloped land are all places the 12 RT excels. The rubber tracks provide maximum traction and floatation in soft, muddy terrain maximizing efficiency when steering or on uneven ground. A guarantee of productivity.

The 12 RT dump body has a large target area to provide consistent high load-carrying capacity up to 22,000 lbs. Low ground pressure ensures minimal impact when traveling across soft terrain. Dual lift cylinders are positioned to provide maximum leverage and lateral stability on uneven ground. The hoist angle gives clean material discharge which maximizes production and avoids the waste of carry-back.

The large two-person cab offers a comfortable working space for both the operator and a passenger with good visibility in all directions. Designed with user friendly controls for ease of operation the 12 RT delivers an automotive feel with the industrial strength you would expect from Kässbohrer.











Technical specifications



Engine

Туре	Cummins QSB 6.7 diesel
Aspiration	Turbocharged and aftercooled
No. of cylinders	6
Displacement	408 in ³ / 6.7 l
Power output (ECE)	180 kW / 244 hp
Max. torque	697 lb ft (945 Nm) at 1,500 rpm
Fuel Tank	57 gal / 215 l

Driving characteristics

Speed Low		3 mph / 5 kmh
Speed High		8.7 mph / 14 kmh
Fording depth		42" / 1060 mm
Turning radius		0°
Ground	empty	4.83 psi / 0.34 kg / cm ²
pressure	loaded	6.54 psi / 0.46 kg / cm ²

Cabin

ROPS / FOPS
Ergonomic comfort cabin
Air conditioning and climate control
Suspension drivers seat
Backup camera

Electrics

Voltage		24 V
Alternator		100 A
Batteries	2 x 12 v	Ah 143

Transmission

Hydrostatic	Variable displacement axial
	piston pumps (2 x 26 cm ³)
Final drive	Planetary with
	multidisc brake
Steering control	Steering wheel
	Single joystick (optional)

Dimensions

Overall length	230" / 5,830 mm
Overall width	117" / 2,960 mm
Clearance height	131" / 3,330 mm
Ground clearance	24" / 610 mm
Transport height	122" / 3,100 mm
Dump body loading height	78" / 1,970 mm
Dumping height	30" / 770 mm

Tracks

Туре	Rubber (endless)
Width	29.5" / 750 mm

Weights

9	
Tare weight	31,350 lbs
	14,250 kg
Max. Payload	24,200 lbs
	11,000 kg
Dump body payload	22,000 lbs
	10,000 kg
Dump body cap. (heaped)	8.5 yd ³ / 6.5 m ³
Dump body cap. (level)	528 gal / 2,000 l

Chassis

Type	High strength steel frame
Suspension	Crawler style
Wheels	Steel bogies (16
Track tensioner	Grease filled cyl, spring assis
Central greasing	g system (24 V pump)

Auxiliary hydraulics

Working pump	Gear type 2.0 in ³ / 33 cm ³
Flow capacity	19 gpm / 73 l / min
Control	Joystick
Hydraulic tank	47 gal / 180

Configurations



Rear tip dumper



Side tip dumper



Carrier with crane



The PowerBully Network

Kässbohrer All Terrain Vehicles, Inc.

8850 Double Diamond Parkway Reno, NV 89521 Tel. (775) 857-5000 Fax. (775) 857-5020 contact@powerbully.com www.powerbully.com

Soft Track Supply Inc. / PowerBully

A Division of Kässbohrer All Terrain Vehicles, Inc.
10 Curtis Ct. S.W.
Cartersville, GA 30120
Tel. (770) 386-6984
Fax. (770) 386-6890
contact@powerbully.com
www.powerbully.com

On the details in this catalogue: there may have been product changes after this issue went to print. The images also include accessories and special equipment, which are not supplied as standard. The printing process may cause colour deviations. Statements on compulsory, legal and fiscal regulations and implications are only valid for the Federal Republic of Germany. Therefore, please ask your contact at Kässbohrer Geländefahrzeug AG for the final status. Printed in USA.



of Kässbohrer Geländefahrzeug AG.



