



Pisten Bully 300 Specifications

Dimensions	Width	without tracks with aluminum tracks with steel tracks with multiflex tiller	2,500mm 4,160mm 4,160mm 5,400mm
	Height with tilted cab		3,325mm
	Overall height		2,880mm
	Ground clearance		approx. 350mm
	Load area		2,300mm x 1,920mm
Weight	Dead weight with combined tracks Dead weight with steel tracks Gross weight incl. auxiliary equip. Loading area payload without aux. equip.		6,700kg 6,900kg 10,200kg 1,650kg
Engine	Type Cylinders Capacity Power according to ECE Max. torque Average fuel consumption Tank capacity		Mercedes Benz, OM 926 LA 6 7,200 cm ³ 240 kW (330 ECE-bhp) 1,300 Nm/1200-1,600rpm 16 l/h 190 l
Brakes	Using hydromatic transmission, with no mechanical wear. Two multi-disk parking/holding brakes.		
Electrical	Low voltage unit Alternator Batteries Cold start power		24 volt 28 V/120 A 2 x 12 V/135 Ah 600 A
Operational Data	Speed, infinitely variable Specific surface press. with alum. tracks Specific surface press. with steel tracks Hourly coverage		0-21 km/h 0.049kg/cm ² 0.050 kg/cm ² 90,000 m ² /h (with tiller)
Auxiliary Equipment			
Front	All-Way blade, Kahlbacher rotary snowblower, SnowCutter, Pipe Magician, Snow Bucket, Blade Loader.		
Rear	Multiflex Tiller, Flexible Compactor Bar. 4-, 8-, 18-, 20- passenger cabin.		