



Pisten Bully 600 Specifications

Pisten Bully 600 Specifications	
Dimensions	
Width without chains	2,500 mm
over combined tracks	4,202 mm
over steel tracks	4,202 mm
using finisher and MultiFlex tiller	5,400 mm
Height	
Height above winch ready for operation	3,280 mm
Height with tilted driver's cab	3,360 mm
Overall height	2,880 mm
Length with All-Way blade and MultiFlex tiller	10,075 mm
Ground clearance	350 mm
Loading platform	2,250 x 1,920 mm (4.3 m ²)
Weight	
Tare weight with combined tracks	9,000 kg
Tare weight with steel tracks	9,200 kg
Admissible total weight incl. additional equipment	11,000 kg
Payload on platform without winch	2,500 kg
Performance Data	
Speed in winch mode	0-17 km/h 3-stage
Speed with winch mounted	0-20 km/h
Specific ground pressure with combined tracks	0.063 kg/cm ²
Specific ground pressure with steel tracks	0.064 kg/cm ²
Ground coverage with MultiFlex tiller	96,000 m ² /h
Engine	
Type	Mercedes-Benz OM 460 LA
Cylinders	6
Displacement	12.8 l / 12,800 cc
Power output (ECE)	295 kW (400 hp)
Max. torque	1,900 Nm at 1,300 rpm
Fuel consumption from	20 l/h
Fuel tank capacity	220 l (80 l additional tank)
Brakes	
	Non-wearing by means of hydrostatic drive train. Two multi-disk brakes as parking brake.
Electrics	
Low-voltage system	24 Volt
Alternator	28 V / 140 A
Batteries	2 x 12 V / 135 Ah
Cold-start rating	600 A