

Pressure Pot

Pavement marking machine

Technical data

	Advantage 500	Advantage 800
Truck Chassis		
Chassis Model	Isuzu FVR	Peterbilt 520
US Truck Class	7	8
Chassis GVWR	33,000 lbs	60,000 lbs
Chassis Engine	Cummins B6.7 (6.7L)	Paccar PX-9 (8.9L)
Chassis Engine Performance	260 HP (2,400 1/min)	360 HP (2,000 1/min)
Front Axle & Suspension Type	Dana E-1254W steer axle, 12k GAWR	Paccar FX-20 steer axle, 20k GAWR
Rear Axle & Suspension Type	Air spring Dana S21-140, 21k GAWR	–
Chassis Wheelbase	14‘ 2“	14‘ 2“
Overall Truck Length (Approx.)	32‘	35‘
Overall Truck Height (Approx.)	11‘	11 1/2‘
Turning Radius (Curb to Curb)	23.7‘	32‘
Fuel Type	Diesel	Diesel
Fuel Tank Size	50 gal	80 gal
Equipement Platform		
Material of Construction	Aluminum	Structural steel
Deck Surface	Flat sheet aluminum with abrasive grip tape	Flat sheet steel with abrasive grip tape
Overall Width	8‘	8‘
Overall Length	18‘ 6“	21‘ 3“
Riser Height	8“	8“
Equipement Utilities		
Auxiliary Engine	74 hp Tier 4F diesel engine	74 hp Tier 4F diesel engine
Air Compressor Model	BOSS 210 utility skid rotary screw compressor	BOSS 210 utility skid rotary screw compressor
Air Dryer	Schmidt coalescing dryer	Schmidt coalescing dryer

	Advantage 500	Advantage 800
Hydraulic Pump	Gear Pump, engine aux drive	Gear Pump, engine aux drive
Hydraulic System Type	Closed center, with return filter	Closed center, with return filter
Hydraulic Reservoir	10 gal	10 gal
Cleaner System		
Cleaner Tank Type	Stainless steel ASME	Stainless steel ASME
Cleaner Tank Capacity	20 gal	40 gal
Gun Flushing	Manual 3-way valve gun flushing in Console	Manual 3-way valve gun flushing in Console
Application Material System		
Material Tank Type	Stainless steel ASME with hydraulic agitator	Stainless steel ASME with hydraulic agitator
Material Tank Quantity	2	2
Material Pumps	2“ MB Diaphragm pumps with PTFE seals and balls	2“ MB Diaphragm pumps with PTFE seals and balls
Material Plumbing	2“ Stainless steel sanitary process plumbing	2“ Stainless steel sanitary process plumbing
Material Manifold Filter	Stainless steel with sanitary clamp end and 100 sq in filter	Stainless steel with sanitary clamp end and 100 sq in filter
Glass Bead System		
Glass Bead Tank Type	Steel ASME with (3) sight gauges	Steel ASME with (3) sight gauges
Glass Bead Tank Quantity	1	1
Glass Bead Tank Capacity	3,000 lbs	5,000 lbs
Glass Bead Loading	Vacuum fill with jet pump	Vacuum fill with jet pump
Loading Rate	200 lbs/min	200 lbs/min
Glass Bead Plumbing	2“ Sanitary and/or NPT	2“ Sanitary and/or NPT
Glass Bead Manifold	Steel with sanitary clamp end	Steel with sanitary clamp end
Glass Bead & Paint Guns, Air Blowers		
Paint Guns	Kamber 38-15	Kamber 38-15
Paint Gun Quantity	4	4
Glass Bead Guns	Kamber 90HO	Kamber 90HO
Glass Bead Gun Quantity	3	3
Air Blowers	3	3
Outrigger & Carriage Type		
Outrigger Location	Rear	Rear
Carriage Style	Linear bearing vertical lift with pneumatic cylinders	Linear bearing vertical lift with pneumatic cylinders
Outrigger Travel	48“	48“
LH Carriage Wheel Quantity	2	2
RH Carriage Wheel Quantity	1	1
Operator Area		
Operator Cover Type	Canopy	Canopy
Operator Seats	(2) Air ride vinyl high back seats	(2) Air ride vinyl high back seats
Control Box Mounts	Weatherproof enclosures on RAM ball mounts	Weatherproof enclosures on RAM ball mounts
Equipment Controls		
Outrigger Steering	Tilting & telescoping steering columns	Tilting & telescoping steering columns
Operator Console	Single rear console	Single rear console
Skip Timer Control Boxes	(2) Skipline SC-12	(2) Skipline SC-12
Digital Speed Meter	In front cab	In front cab
Lighting		
Cab Lights	Amber LED light bar	Amber LED light bar
Platform ICC Lights	3/4“ LED Marker lights	3/4“ LED Marker lights
Carriage Lights	Red/white flashers	Red/white flashers
Safety		
Fire Extinguishers	(1) 5# in cab / (1) 10# on platform	(1) 5# in cab / (1) 10# on platform
Ladders	(3) Ladders and rear steps	(3) Ladders and rear steps
Platform Railings	42“ Square tube railing / rounded corners / bolt-on	42“ Square tube railing / rounded corners / bolt-on

	Urbanliner 120	Urbanliner 240
Truck Chassis		
Chassis Model	Isuzu NRR	Isuzu FTR
US Truck Class	5	6
Chassis GVWR	19,500 lbs	25,900 lbs
Chassis Engine	Isuzu 4HK1-TC (5.19L)	Cummins B6.7 (6.7L)
Chassis Engine Performance	215 HP (2,500 1/min)	260 HP (2,400 1/min)
Front Axle & Suspension Type	Leaf spring steer axle, 7.3k GAWR	Dana E-1254W steer axle, 12k GAWR
Rear Axle & Suspension Type	Leaf spring axle, 13.7k GAWR	Air spring Dana S19-140, 19k GAWR
Chassis Wheelbase	11‘ 1“	12‘ 8“
Overall Truck Length (Approx.)	26‘	28‘
Overall Truck Height (Approx.)	10 1/2‘	11‘
Turning Radius (Curb to Curb)	20‘	21.8‘
Fuel Type	Diesel	Diesel
Fuel Tank Size	30 gal	50 gal
Equipement Platform		
Material of Construction	Structural steel	Structural steel
Deck Surface	Flat sheet steel with abrasive grip tape	Flat sheet steel with abrasive grip tape
Overall Width	7‘ 9“	8‘
Overall Length	15‘	16‘ 8“
Riser Height	7 1/2“	8“
Equipement Utilities		
Auxiliary Engine	74 hp Tier 4F diesel engine	74 hp Tier 4F diesel engine
Air Compressor Model	BOSS 210 utility skid rotary screw compressor	BOSS 210 utility skid rotary screw compressor
Air Dryer	Schmidt coalescing dryer	Schmidt coalescing dryer
Hydraulic Pump	Gear Pump, engine aux drive	Gear Pump, engine aux drive
Hydraulic System Type	Closed center, with return filter	Closed center, with return filter
Hydraulic Reservoir	10 gal	10 gal
Cleaner System		
Cleaner Tank Type	Stainless steel ASME	Stainless steel ASME
Cleaner Tank Capacity	10 gal	20 gal
Gun Flushing	Manual 3-way valve gun flushing in Console	Manual 3-way valve gun flushing in Console
Application Material System		
Material Tank Type	Stainless steel ASME with hydraulic agitator	Stainless steel ASME with hydraulic agitator
Material Tank Quantity	2	2
Material Pumps	1-1/2“ MB Diaphragm pumps with PTFE seals and balls	1-1/2“ MB Diaphragm pumps with PTFE seals and balls
Material Plumbing	2“ Stainless steel sanitary process plumbing	2“ Stainless steel sanitary process plumbing
Material Manifold Filter	Stainless steel with sanitary clamp end and 100 sq in filter	Stainless steel with sanitary clamp end and 100 sq in filter
Glass Bead System		
Glass Bead Tank Type	Steel ASME with (3) sight gauges	Steel ASME with (3) sight gauges
Glass Bead Tank Quantity	1	1
Glass Bead Tank Capacity	1,000 lbs	1,500 lbs
Glass Bead Loading	Vacuum fill with jet pump	Vacuum fill with jet pump
Loading Rate	200 lbs/min	200 lbs/min
Glass Bead Plumbing	2“ Sanitary and/or NPT	2“ Sanitary and/or NPT
Glass Bead Manifold	Steel with sanitary clamp end	Steel with sanitary clamp end
Glass Bead & Paint Guns, Air Blowers		
Paint Guns	Kamber 38-15	Kamber 38-15
Paint Gun Quantity	4	4
Glass Bead Guns	Kamber 90HO	Kamber 90HO
Glass Bead Gun Quantity	3	3
Air Blowers	3	3

	Urbanliner 120	Urbanliner 240
Outrigger & Carriage Type		
Outrigger Location	Rear	Rear
Carriage Style	Parallel linkage lift with pneumatic cylinder	Linear bearing vertical lift with pneumatic cylinders
Outrigger Travel	48“	48“
LH Carriage Wheel Quantity	1	2
RH Carriage Wheel Quantity	1	1
Operator Area		
Operator Cover Type	Canopy	Canopy
Operator Seats	(2) Air ride vinyl high back seats	(2) Air ride vinyl high back seats
Control Box Mounts	Weatherproof enclosures on RAM ball mounts	Weatherproof enclosures on RAM ball mounts
Equipment Controls		
Outrigger Steering	Tilting & telescoping steering columns	Tilting & telescoping steering columns
Operator Console	Single rear console	Single rear console
Skip Timer Control Boxes	(2) Skipline SC-12	(2) Skipline SC-12
Digital Speed Meter	In front cab	In front cab
Lighting		
Cab Lights	Amber LED light bar	Amber LED light bar
Platform ICC Lights	3/4“ LED Marker lights	3/4“ LED Marker lights
Carriage Lights	Red/white flashers	Red/white flashers
Safety		
Fire Extinguishers	(1) 5# in cab / (1) 10# on platform	(1) 5# in cab / (1) 10# on platform
Ladders	(2) Ladders and rear steps	(3) Ladders and rear steps
Platform Railings	42“ Square tube railing / rounded corners / bolt-on	42“ Square tube railing / rounded corners / bolt-on

aebi schmidt group

Aebi Schmidt North America Inc.
201 MB Lane
Chilton, WI 53014, USA
Phone: +1 800 558 5800
www.aebi-schmidt.com

© Aebi Schmidt Group
All rights reserved.
Technical data is subject to change.
Illustrations are not binding.
Errors and amendments excepted.

Document created on 7 OCT 2026

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com