

SEL
Under Tailgate Spreader



*SEL-C shown with center drop port

The S-Series Under Tailgate Spreaders have height-adjustable spinners and are designed to install below the existing tailgate. This provides a variety of spreading solutions when the dump body is higher than 44 inches above the ground.

- Designed for 15,000+ GVW trucks with ground clearances greater than 44 in.
- Works with 96 in. wide dump bodies
- Utilizes truck's electric system so no expensive hydraulic system is needed
- Mounts below dump body tailgate

Highlights

- Rugged 6 in. auger with continuous/reverse flighting to unload from both sides of the dump body
- Independent hydraulic control of auger and spinner
- Direct drive higher performance and lower maintenance
- 18 in. poly spin disc broadcasts up tp 40 ft.
- Available with standard or extreme left or right discharge
- Stainless steel or carbon steel construction
- Stabilizer kit keeps spinner parallel to the road at all dump angles
- Tailgate shields
- Made in the USA

Specifications

Size	96 in. width
Conveyor	6 in. auger with continuous flighting
Drive	Electric
Weight Empty	457 lbs.
Construction	10 gauge carbon steel or 10 gauge stainless steel
Spread Width	4–30 ft.
Safety Features	Electric safety interlock
Warranty	1 year
Controller	Included

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com