From series 2025

NEW



Ready to

REMOVE

TECHNICAL SPECIFICATIONS

BeachTech 3000 Facelift







BeachTech®

BeachTech 3000 Facelift

Engine power tractor
74 kW (100 hp)

Working width
8 ft 2 in

Hopper volume
6.2 cu yd

Area coverage
7.4 acres/hr



Cleaning method	**patented raking-/ screening-/ mixed technique**	
Tractor requirements	**engine power min.****	74 kW (100 hp)
	four-wheel drive	
	differential lock	
	tires	19.6” front, 23.6” back
	coupling for drawbar eye Ø 40 mm, height adjustable to approx. 3 ft 3 in height	
	PTO shaft	6 spline (21 spline), 1 3/8”
	power take-off, AR NORM	540 rpm (1000 rpm possible)
	power supply	standardized socket, 12 V
	drawbar load	3307 lbs
Dimensions	**vehicle lengths, in operation**	22 ft 11 in
	vehicle lengths, road transport	18 ft 8 in
	vehicle width, road transport	8 ft 11 in
	working width	8 ft 2 in
	vehicle height	7 ft 10 in
	vehicle height, road transport	12 ft 11 in
	Unloading height dump body	5 ft 1 in
Tires	**low pressure tires, wide (standard)**	500/60-22,5
Weight	**empty weight**	7,055 lbs
	technically permissible total weight*	14,330 lbs
Tank capacity	**hydraulic oil**	10.6 US gal
Performance	**area coverage up to****	7.4 acres/hr
Working depth	**working depth up to****	12 in
Capacity	**collecting hopper**	0.9 cu yd
	dump body	5.3 cu yd
Speed	**operating speed max.****	7.5 mph
	road traffic*	25 mph

Subject to change in the course of technical development. The images shown are for illustration purposes only and may contain optional extras.

Dealer stamp

* according to local traffic regulations
** depending on soil / beach conditions

Tel.: +49 7392 900 - 461
E-Mail: info@beach-tech.com
www.beach-tech.com

BeachTech®

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com