

PV Series

Spreader

Technical data

	LPV	PV	Polyhawk
Hopper			
Hopper capacity	0.23 - 0.38 m³*	1.15 - 1.53 m³*	1.15 - 1.53 m³*
Conveyor system			
Conveyor system	Belt over chain	Drag chain / Belt over chain	Drag chain
Distribution system			
Distribution systems	Poly spreading disc: Spreading disc diameter: 36 cm Spreading width: 914 cm	Poly spreading disc: Spreading disc diameter: 36 cm Spreading width: 914 cm	Poly spreading disc: Spreading disc diameter: 36 cm Spreading width: 914 cm
Mounting/demount system			
Mounting/demount system	Fixed-mounted	Fixed-mounted	Fixed-mounted
Drive system			
Type of drive	electric / Hydraulic / Engine drive	gas / electric / Hydraulic / Engine drive	Hydraulic / gas / Engine drive
Dimensions			
Hopper length	914.4 - 1,524 mm*	1,828.8 - 2,438.4 mm*	1,828.8 - 2,438.4 mm*
Hopper width	1,270 mm*	1,270 mm*	1,270 mm*
Hopper height	889 mm*	889 mm*	889 mm*

Aebi Schmidt Holding AG | CH-8152 Glattpark, Switzerland
www.aebi-schmidt.com

© Aebi Schmidt Group | All rights reserved. Technical data is subject to change. Illustrations are not binding. Errors and amendments excepted.

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com