from series 2024



Ready to

REMOVE

TECHNICAL SPECIFICATIONS

BeachTech 1000







BeachTech®

BeachTech 1000

Engine power
from 25 kW | 35 hp

Working width
1.250 mm

Hopper volume
0,4 m^3

Area coverage
up to 10.000 m^2/h



Cleaning method	**Screening technique with vibrating screen and transport system**	
Tractor requirements	**Engine power min.****	25 kW (35 hp)
	Four-wheel drive	
	differential lock	
	3-point hitch, cat. 1 or cat. 2	
	PTO shaft	Z6, 1 3/8“
	power take-off, AR NORM	540 rpm
	power supply	12 V
Dimensions	**vehicle length, road transport**	3.400 mm
	vehicle width, road transport	1.750 mm
	working width	1.250 mm
	vehicle height	1.800 mm
	Unloading height collecting hopper	0 – 1.600 mm
Tires	**low pressure tires, wide**	24 x 13.00 – 12
Weight	**Empty weight**	1.220 kg
	Technically permissible total weight*	2.000 kg
Tank capacity	**hydraulic oil**	70 l
Performance	**area coverage up to****	10.000 m^2/h
Working depth	**working depth up to****	10 cm
Capacity	**collecting hopper**	0,4 m^3
Speed	**operating speed max.****	8 km/h
	road traffic*	25 km/h

* according to local traffic regulations

** depending on soil / beach conditions

Subject to change in the course of technical development. The images shown are for illustration purposes only and may contain optional extras.

dealer stamp

BeachTech®
Tel.: +49 7392 900 - 461
E-Mail: info@beach-tech.com
www.beach-tech.com

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com