from series 2024



Ready to

REMOVE

TECHNICAL SPECIFICATIONS

BeachTech 2500







BeachTech®

BeachTech 2500

Engine power
from 59 kW | 80 hp

Working width
2.500 mm

Hopper volume
2,8 m³

Area coverage
up to 30.000 m²/h



Cleaning method	**patented raking-/ screening-/ mixed technique**	
Tractor requirements	**engine power min.****	59 kW (80 hp)
	four-wheel drive	
	differential lock	
	tires	480 mm front, 520 mm back
	2-point hitch, cat. 2	
	PTO shaft	Z6, 1 3/8“
	power take-off, AR NORM	540 rpm (1000 rpm possible)
	power supply	standardized socket, 12 V
	1 double-acting circuit of the additional tractor hydraulics in standard	
Dimensions	**vehicle lenght, road transport**	5.600 mm
	vehicle width, road transport	2.500 mm
	working width	2.500 mm
	vehicle height	2.250 mm
	unloading height collecting hopper	2.750 mm
Tires	**low pressure tires, wide (standard)**	520/50 – 17
Weight	**empty weight**	2.790 kg
	technically permissible total weight*	4.000 kg
Tank capacity	**hydraulic oil**	30 l
Performance	**area coverage up to****	30.000 m²/h
Working depth	**working depth up to****	30 cm
Capacity	**collecting hopper**	2,8 m³
Speed	**operating speed max.****	12 km/h
	road traffic*	25 / 40 km/h

* according to local traffic regulations

** depending on soil / beach conditions

Subject to change in the course of technical development. The images shown are for illustration purposes only and may may contain optional extras.

dealer stamp

BeachTech®
Tel.: +49 7392 900 - 461
E-Mail: info@beach-tech.com
www.beach-tech.com

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com