

Sidewing

Snow plough

Technical data

	9‘ low profile	10‘	10‘ low profile
Construction			
Number of blades	1	1	1
Dimensions			
Plough height right	812 mm	965 mm	838 mm
Plough height left	660 mm	787 mm	660 mm
Length at cutting edge	2,743 mm	3,048 mm	3,048 mm
Total width	2,895 mm	3,225 mm	3,175 mm
Operational Dimensions			
Clearing width	–	1,219 mm at 23° 1,498 mm at 30° 1,727 mm at 34° 1,955 mm at 40°	1,219 mm at 23° 1,498 mm at 30° 1,727 mm at 34° 1,955 mm at 39°
Weights			
Approx. weight with steel cutting edges	161 kg	303 kg	182 kg

	11‘	12‘
Construction		
Number of blades	1	1
Dimensions		
Plough height right	990 mm	1,016 mm
Plough height left	787 mm	787 mm
Length at cutting edge	3,352 mm	3,657 mm
Total width	3,530 mm	3,835 mm
Operational Dimensions		
Clearing width	1,346 mm at 23° 1,676 mm at 30° 1,905 mm at 34° 2,057 mm at 36°	1,803 mm at 30° 2,032 mm at 34° 2,311 mm at 40°

	11‘	12‘
Weights		
Approx. weight with steel cutting edges	334 kg	354 kg

Aebi Schmidt Holding AG
Lindbergh-Allee 1
CH-8152 Glattpark, Switzerland
Phone: +41 44 308 58 00
www.aebi-schmidt.com

© Aebi Schmidt Group
All rights reserved.
Technical data is subject to change.
Illustrations are not binding.
Errors and amendments excepted.

Document created on 10 JUL 2026

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com