

H2000

Snow blower

Technical data

Clearing head	
Clearing width	115“ / 120“ / 128“
Clearing capacity up to approx.	1,500 t/h
Ejection distance up to approx.	120‘
Rotation of discharge chute	140°
Ribbon drive	
Type of drive	hydrostatic
Displacement pump - capacity	7.9 in^3/rpm
Displacement pump - maximum pressure	5,075 PSI
Drive system	
Engine type	Caterpillar C7.1
Number of cylinders	6
Exhaust emission	Tier 4 Final
Fuel	Diesel
Fuel tank	90 gal
Displacement	427.7 in^3
Performance	320 HP
max. Torque	935 ft-lbs
Dimensions	
Clearing head height	58“
Ribbon diameter	38“
Impeller diameter	46“
Total length	11‘ 1“
Weights	
Weight approx. (Depending on equipment and size)	12,100 lbs
Min. tipping load carrier vehicle in swiveled position	26,000 lbs

aebi schmidt
group

Aebi Schmidt North America Inc.
201 MB Lane
Chilton, WI 53014, USA
Phone: +1 800 558 5800
www.aebi-schmidt.com

© Aebi Schmidt Group
All rights reserved.
Technical data is subject to change.
Illustrations are not binding.
Errors and amendments excepted.

Document created on 11 JUL 2026

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com