BOSSTEK

The DB-10 is designed for indoor and outdoor demolition sites creating airborne dust particles. With wheel barrow mobility and a grounded, wall-outlet power connection, the system is ready to control dust with little to no hassle.

DUSTBOSS® DB-10

DB-10

SPECIFICATIONS

GENERAL SPECIFICATIONS

- Throw: 30 feet (10 m) at 20° throw angle.
- Fan: 3355 CFM.
- Adjustable throw angle: 0° - 50°.
- Nozzles: 12 brass.
- Droplet size: 50 - 95 micron.
- Water connection: 5/8" garden hose.



ELECTRICAL SPECIFICATIONS

- U.S.: Single phase / 0.75 HP fan / 120 volt / 60 hertz / 5.8A (4.88A measured).

DIMENSIONS

(Standard: carriage mount)

- 2.58 feet (30.96 inches or 0.79 meters) wide.
- 2.75 feet (33.00 inches or 0.84 meters) long.
- 3.58 feet (42.96 inches or 1.09 meters) tall.
- 120.00 lbs. (54.43 kilograms).

NOISE

- 68 decibels.

WATER TABLE

ENGLISH UNITS			
Supplied Water Pressure, PSI	40	60	100
Water Flow, GPM	.20	.24	.35

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com