

swenson
a brand of aebi schmidt

EV Dual Auger

Spreader

This dual auger, heavy-duty spreader system delivers extreme durability under the harshest conditions. The strength and reliability of the EV Dual Auger system are designed to be extremely versatile, requiring less maintenance and adjustment. It offers consistent operation with a wide range of spreading materials. This dual auger, heavy-duty system will get the job done in the toughest conditions — mile after mile.

Highlights

- **Advanced Augers:** Heavy-duty 7” hard-surfaced augers with stepped flights
- **Truck Compatibility:** Designed for 20,000+ GVW trucks
- **Versatile Spinner:** Swing-up spinner system allows for quick unloading of material

Your benefits

- **Hydraulic-Driven Spreader:** With a 3:6:1 gearbox ratio
- **Tapered Inverted V:** Keeps weight off the augers to optimize performance
- **Hydraulic Interlock System:** This safety feature prevents access to the auger drive system while it’s in operation

This document has been machine-translated from the original German version.

Performance features

Concept

Keep moving and get the job done faster. Built to last, the EV Dual Auger System combines strength and reliability with an advanced design to quickly and evenly unload most materials with power and efficiency. The optional heavy-duty Drop ‚n' Lock top screen breaks up material to prevent damage to the auger drive system and avoid tunneling.



Pre-Wet Systems

The EV Dual Auger V-Box Spreader is available with hydraulic or electric pre-wet systems, providing the right solution for the materials you use.

Dosage and Conveyor Systems

The EV Dual Auger can reliably handle rock salt, sand, salt/sand mix, 3/8 chips, magnesium chloride, Clear Path Ice Melt, and treated rock salt.

Related products

EV Select

Spreader



EVA Auger

Spreader



This document has been machine-translated from the original German version.



Swenson products are designed for reliable performance in demanding conditions, ensuring safe and efficient operations throughout the year.

Technical data

	EVDA	EVDAF
Hopper		
Hopper capacity	3.4 - 8.8 m^3	3.4 - 8.8 m^3
Pre-wet equipment		
Tank capacity lateral tanks	340.69 / 3,217.6 l*	340.69 - 3,217.6 l*
Conveyor system		
Conveyor system	Dual auger	Dual auger
Distribution system		
Distribution systems	Spreading disc: Spreading width: 122 - 1,219 cm	Spreading disc: Spreading width: 122 - 1,219 cm
Mounting/demount system		
Mounting/demount system	Demount legs / Fixed-mounted / Chassis mount	Demount legs / Fixed-mounted / Chassis mount
Drive system		
Type of drive	Vehicle hydraulics	Vehicle hydraulics
Control system		
Control system	Open and close loop	Open and close loop
Dimensions		
Hopper length	2,438.4 - 4,876.8 mm*	2,438.4 - 4,876.8 mm*
Hopper width	2,082.8 - 2,133.6 mm*	2,082.8 - 2,133.6 mm*
Hopper height	1,219.2 - 1,574.8 mm*	1,219.2 - 1,574.8 mm*

aebi schmidt group

Aebi Schmidt Holding AG
Lindbergh-Allee 1
CH-8152 Glattpark, Switzerland
Phone: +41 44 308 58 00
www.aebi-schmidt.com

© Aebi Schmidt Group
All rights reserved.
Technical data is subject to change.
Illustrations are not binding.
Errors and amendments excepted.

Document created on 10 JUL 2026

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com