

STCC™ Specialty Cross Conveyor

The most efficient method of distributing granular materials available today.

- Designed for for Class 7 + trucks (26,000 GVW) 102 in. trough fits standard width dump bodies
- An all-around performer designed for year round use including trench filling, shouldering, road sander and asphalt patching
- Perfect for asphalt applications*
- 14 in. wide high-temp belt-over-chain allows most materials to be easily conveyed



Highlights

- Hydraulic control
- Quick detach 24 in. extension plate can be used on either side of conveyor
- 24 in. extension positions material outside of tire path
- Adjustable feedgate allows precise material output adjustment, even when loaded
- Stabilizer kit (optional) keeps spinner (optional) parallel to the road at all dump angles
- Hinged top cover makes dump truck functional while not spreading
- Stainless steel or carbon steel construction
- Made in the USA

Specifications

Size	102 in. width
Conveyor	14 in. high temp belt-over-chain
Drive	Hydrualic
Weight Empty	1,100 lbs.
Construction	Carbon steel or Stainless steel
Safety Features	Hinged top cover, optional lightbar, optional legstands
Warranty	1 year
Accessories	Leg stands, reversing valve, spinner system, 4 ft. motorized extension, light bar
Controller	Purchased separately

**Accommodates salt/sand mix with optional spinner assembly. Not recommended for straight salt applications due to high volume output.*

TELEMET
Efficiency Through Simplicity™

Advice, spare parts and service

Telemet · Office in Chile

Los Canteros 8723, La Reina, Santiago 7880414, Chile

Phone +56 22 356 2735

info@telemet.com

telemet.com